HANDED BY THE SEAT Model MX QSI-6233-BF 0.75 in. Quick Ship Inventory program SUBMITTAL DATA SIDE VIEW FRONT VIEW SS. Curtain Rod ·32<u>3</u>" w/ Receiver Cups. 0 36" x 8" Backng Opposite Seat For Future Grab Bar 36"x 1 1/2" SS. Grab Bar 22" x 1 1/2" 73<u>3</u>" SS. Grab Bar 78-17" 78<u>1</u>" 66<u>3</u>\* æ ∘ 344 TH 347 TH 30<u>3</u>" 26" x 21" Frameless  $18\frac{3}{4}$ HDPE Fold Up Seat ž 60" -31" Location of ArmorCore -62" Roll-In Shower Stall TOP VIEW The shower enclosure shall be MAAX model QSI 6233 BF-F center, right or left. Finished surface shall be of an applied acrylic. The base shall be attached to the sump of the unit in 32<u>3</u>' such a manner to form an integral part with an inner and outer coating of polyester resin. The unit shall have outside dimensions of  $62" \times 32 3/4" \times 78 1/2"$ . The unit meets ADA, ANSI A117.1, ANSI Z124.1.2, UPC, CSA B45.5, HUD-UM73, and Home Innovation Research Lab. This enclosure shall be equipped with the following installed accessories: 1) One 36" x 1 1/2" diameter stainless steel horizontal grab bar on the back wall, 2) One 22" x 1 1/2" diameter stainless steel horizontal grab bar on the side wall, both with 1 1/2" statute clearance, mounted with stainless steel bolts, and secured from the rear with  $3^{"} \times 3^{"} \times 11$  gauge metal mounting plates, 3)  $26^{"} \times 21^{"}$  frameless white HDPE fold up seat. 4) One inch diameter, 18 gauge stainless steel curtain rod with receiver cups, 5) Backing for future vertical grab bar opposite the seat, (by others), 6) Factory installed Armor Core,  $\oplus$ 7) 3/4" COL threshold. Available Options: 8) Valve package includes: Hand held shower set, swivel connector, 60" flex hose, vacuum breaker, 30" slide bar, wall water outlet fitting, 9) Green anti-bacterial shower 31 curtain and hooks, 10) White shower curtain and hooks. 11) Nurses call box drilling. This unit features the outside dimensions of 62" of overall width. This does not allow for full enclosure of This may require the need to notch study for all seat in place. This may require the need to notch study to allow for bolt clearance for installation. For a dry wall enclosed fire wall installation, adjustment of the wallboard may be necesary to provide clearance of the bolts while maintaining the integrity of the drywall fire wall enclosure. 6' -4"+ 15<u>3</u>' 17 NOTE: THIS UNIT WILL NOT ACCEPT A DOOR. CENTER OF DRAIN ADA ALLOWED 1/2" (1:2) CHANGE IN LEVEL ACRYLIC ARMOR CORE Гą FLOORING XIIIII DUE TO THE NATURE OF THE MATERIALS DIMENSIONS MAY VARY  $\pm \ 1/2"$  $\overline{}$ L3/8" 5 DRAIN CUT-OUT SIZE 10" DIA. x 1/2" DEEP RECESS, PLUS 6" DRAIN CORE. Drawing#:

MX QSI-6233-BF 0.75 in.

